



技术参数 Datasheet	
发射器型号: Transmitter model:	TCT – B08
操作元件及功能: Operating elements:	最多 8 个单档按键 1 个压紧型急停开关 Up to 8 one-step push buttons 1 STOP impact switch
尺寸: Dimensions:	193 x 62 x 50mm
重量: Weight:	320g (不含电池) (exclude battery)
工作温度: Operation temperature:	-25°C ~ +70°C(exclude battery)
储存温度: Storage temperature:	-40°C ~ +80°C
工作湿度: Operation humidity:	≤97% RH
外壳材质: Housing material:	高强度工程塑料 High strength engineering plastics
防护等级: Protection degree:	IP54
天线: Antenna:	内置 Internal antenna
专用地址码: Address code:	32bit

通信方式: Digital-electronic:	实时通信 Real-time control
频率范围: Frequency range:	416.800-419.975MHz; 433.100-434.750 MHz
发射功率: Transmitting power:	≤10mW
工作电压: Power supply:	3.3V-5.0VDC (3 节 5 号电池) (3 AA battery)
工作电流: Power current:	≤40mA
工作时间: Battery working Time:	≥40h
自动关机: Automatic power-off:	0-30 分钟可选 0-30 min optional
状态显示: Status indicator:	LED



技术参数 Datasheet	
接收器型号: Receiver model:	TCR – B08
输出方式: Output mode:	最多 12 个全密闭继电器 1 路串联急停继电器 1 路 CANBus 通信 (选配) Up to 12 relays output (on/off) 1 safety E-STOP output CANBus (optional)
尺寸: Dimensions:	248 x 206 x 75mm
重量: Weight:	1250g
天线: Antenna:	外置 External antenna
通信距离: Typical working range:	≥100m
外壳材质: Housing material:	高强度工程塑料 High strength engineering plastics
防护等级: Protection degree:	IP65
安装尺寸: Installation size:	186 x 88mm φ 6mm * 4

电源: Power supply:	42-240VAC 50/60Hz; 10-30VDC or 380VAC
功率: Power consumption:	≤6W
LED:	操作状态指示、射频信号、机构运行指示 Status、RF and operation indication
接口形式: Output type:	线缆或重载连接器 Cable or industrial connector
继电器容量: Relay capacity:	4A/250VAC; 3A/30VDC (resistance load)
可增设功能: Optional function:	多对一功能、一对多功能、多对多功能 Tandem control, N to one、one to N or N to N